

Coating Development Group, Inc.

Floor Coatings

Restore your dirty old floors with **CDG Floor Coatings** for plastic, ceramic and many other surfaces.

Apply a new color coat and give life to those surfaces without the need for major stripping, cleaning or replacement.

CDG Floor Coatings are durable, environmentally friendly and easy to apply.



Just sweep and mop surface

Roll, brush or spray on coatings

Self-crosslinking waterborne materials

Low VOC's and HAP's content

Coverage from 250 to 300 sq. ft./gallon

Easy cleanup

2 or 3-step systems available:

Sealer (optional for maximum adhesion)

Colored basecoats (black, white, grey and beige) 5-gallon minimum order. Custom colors available at a 50% premium and a 50-gallon minimum order.

Clear topcoat (CDG's or comparable brand)

Coating Development Group, Inc.
www.cdgclearkin.com
215-426-6216





Coating Development Group, Inc

Floor Coatings

Floor Preparation and Coatings Applications

Clean of floor tiles, prior to coating application.

- Sweep surface of old floor.
- Mop with soapy water
- Wet mop and dry surface.

Application recommendations

- Roller (short nap)
- Brush
- Spray
- Sponge mop

Drying schedules

- Sealer coat
 - Apply one coat and air dry 16 hours before applying color coats.
- Color coats
 - Apply one - two coats, depending on application and color, with 4-6 hours drying between coats. Drying time is dependent on relative humidity conditions. Longer drying of 8-10 hours may be required above 60% R.H.
- Clear topcoats
 - Apply over color coats and follow directions of manufacturer of clear topcoat. CDG clear topcoats require 16 hours air dry before walking on coated surface.

Equipment Clean-up

- All coatings can be removed from application equipment by washing with soapy water and rinsing with clear water.