

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
 MSDS Number: BD-805
 Version Number
 MSDS Date: APR-09-2012
 Page Number: 1 of 10

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: BLUE CONV. PRIMER
 CAS Number: MIXTURE
 Hazard Rating: Health: 2 Fire: 3 Reactivity: 0 PPI: H

Company Identification: COATING DEVELOPMENT GROUP, INC
 P.O. BOX 14817
 SCHILLER & ALLEN STREETS
 PHILADELPHIA PA 19134-4817

Contact: MARK KOCHANOWICZ
 Telephone/Fax: (215) 426-6216 (215) 426-6219
 Emergency Phone (24 Hour): CHEMTREC
 (800) 424-9300

Product Class: BASECOATS
 Trade Name
 Product Code: BD-805

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
ETHYL ALCOHOL ANHYDROUS HMIS Health: 1 Fire:3 Reactivity:0 PPI:H_____	64-17-5	12.89	
BUTYL ACETATE HMIS Health: 2 Fire:2 Reactivity:0 PPI:H_____	123-86-4	11.38	
XYLENE HMIS Health: 2 Fire:3 Reactivity:0 PPI:H_____	1330-20-7	10.52	
ISOBUTYL ACETATE HMIS Health: 1 Fire:3 Reactivity:0 PPI:H_____	110-19-0	7.99	
ISO BUTYL ALCOHOL HMIS Health: 2 Fire:3 Reactivity:0 PPI:H_____	78-83-1	5.80	

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
 MSDS Number: BD-805
 Version Number
 MSDS Date: APR-09-2012
 Page Number: 2 of 10

ACETONE			67-64-1	5.64
HMIS Health:	1	Fire:3	Reactivity:0 PPI:H_____	
PM ACETATE			108-65-6	5.09
HMIS Health:	2	Fire:2	Reactivity:0 PPI:H_____	
ETHYLBENZENE			100-41-4	2.67
HMIS Health:	2	Fire:3	Reactivity:0 PPI:H_____	
ISOPROPYL ALCOHOL			67-63-0	2.13
HMIS Health:	1	Fire:3	Reactivity:0 PPI:H_____	
IRON OXIDES			1309-37-1	0.65
HMIS Health:	2	Fire:1	Reactivity:1 PPI:H_____	
METHYLPROPYL KETONE			107-87-9	0.43
HMIS Health:	1	Fire:3	Reactivity:0 PPI:C_____	
MINERAL SPIRITS			8052-41-3	0.34
HMIS Health:	1	Fire:2	Reactivity:0 PPI:H_____	
CARBON BLACK			1333-86-4	0.32
HMIS Health:	1	Fire:1	Reactivity:0 PPI:C_____	
COPPER PHTHALOCYANINE BLUE			147-14-8	0.24
HMIS Health:	1	Fire:0	Reactivity:0 PPI:E_____	
N-PROPYL ACETATE			109-60-4	0.17
HMIS Health:	2	Fire:3	Reactivity:0 PPI:H_____	
HI FLASH NAPHTHA			64742-95-6	0.13
HMIS Health:	1	Fire:2	Reactivity:0 PPI:H_____	
FORMALDEHYDE			50-00-0	0.04
HMIS Health:	2	Fire:2	Reactivity:1 PPI:X_____	

*** ALL Ingredients in this product are listed in the T.S.C.A. Inventory

SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT - Exposure may cause eye irritation. Symptoms may include stinging, tearing and redness.

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
MSDS Number: BD-805
Version Number
MSDS Date: APR-09-2012
Page Number: 3 of 10

INGESTION - Harmful or fatal if swallowed. Pulmonary aspiration hazard if swallowed and/or vomiting occurs - can enter lungs and cause damage.

INHALATION - Excessive exposures may cause irritation to eyes, nose, throat, lungs; respiratory tract; central nervous system (brain) effects; headaches, nausea; dizziness, loss of balance and coordination; unconsciousness, coma; respiratory failure and death. Repeated excessive exposures may cause liver effects or damage; kidney effects or damage.

SKIN - Skin absorption of material may produce systemic toxicity. May cause irritation with prolonged or repeated contact. Removes natural oil and fats from skin.

CANCER HAZARDS

CONTAINS ETHYLBENZENE - The International Agency for Research on Cancer (IARC) has listed ethylbenzene as a possible cancer causing agent to animals.

Prolonged or repeated overexposure to ethylbenzene may cause the following: - kidney effects - liver effects - lung effects - pituitary effects - thyroid effects - testicular effects.

CONTAINS FORMALDEHYDE - Inhalation of formaldehyde vapor caused cancer in laboratory animal tests. Refer to Section XI for toxicology information on the OSHA regulated components of this product.

SECTION IV - FIRST AID MEASURES

EYE CONTACT - Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.

INGESTION - DO NOT INDUCE VOMITING! This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Seek medical attention. If possible, do not leave individual unattended.

INHALATION - Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

SKIN CONTACT - Wash affected areas with soap and water. Remove

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
MSDS Number: BD-805
Version Number
MSDS Date: APR-09-2012
Page Number: 4 of 10

contaminated clothing and shoes. Obtain medical attention if irritation persists. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class IB
Flash Range: 1.0F - 185.0F (-17.220C - 85.0C)
Explosive Range: Not Available

Use foam, carbon dioxide (CO2) or dry chemical. Water may not be effective to extinguish fire. Use water spray to cool fire-exposed containers and to protect personnel.

Keep personnel removed from and upwind of fire. Wear full fire-fighting turn-out gear (full bunker gear), and respiratory protection (SCBA). Cool container with water spray.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust.

Eliminate all ignition sources, use explosion-proof equipment. The very fine particles can cause fire or explosion. Vacuum or sweep material and place in a disposal container. Obey all local, state and federal laws regarding chemical spills.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN - Closed containers may explode when exposed to extreme heat. Store away from high temperatures, sparks and flames. Avoid prolonged skin contact. Do not breath spray mist. Ground containers while pouring and limit free fall to a few inches to prevent static sparks. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumalations (such as spray booth residues) by immediate immersion in water. Emptied containers may retain hazardous properties. Do not cut, puncture or weld on or near the container. Store large quantities only in buildings designed

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
 MSDS Number: BD-805
 Version Number
 MSDS Date: APR-09-2012
 Page Number: 5 of 10

to comply with OSHA 1910.106.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
ETHYL ALCOHOL ANHYDROUS	1000.00 PPM	N/est	N/est	N/est	1000.00 PPM
BUTYL ACETATE	150.00 PPM	N/est	200.00 PPM	200.00 PPM	150.00 PPM
XYLENE	100.00 PPM	N/est	N/est	N/est	100.00 PPM
ISOBUTYL ACETATE	150.00 PPM	N/est	N/est	N/est	150.00 PPM
ISO BUTYL ALCOHOL	50.00 PPM	N/est	N/est	N/est	100.00 PPM
ACETONE	500.00 PPM	N/est	750.00 PPM	1000.00 PPM	750.00 PPM
PM ACETATE	N/est	N/est	N/est	N/est	N/est
ETHYLBENZENE	100.00 PPM	N/est	125.00 PPM	125.00 PPM	100.00 PPM
ISOPROPYL ALCOHOL	400.00 PPM	N/est	500.00 PPM	500.00 PPM	400.00 PPM
IRON OXIDES	5.00 mg/M3	N/est	N/est	N/est	10.00 mg/M3
METHYLPROPYL KETONE	200.00 PPM	N/est	250.00 PPM	250.00 PPM	200.00 PPM
MINERAL SPIRITS	100.00 PPM	N/est	N/est	N/est	100.00 PPM

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
 MSDS Number: BD-805
 Version Number
 MSDS Date: APR-09-2012
 Page Number: 6 of 10

CARBON BLACK	3.50 mg/M3	N/est	N/est	N/est	3.50 mg/M3
COPPER PHTHALOCYANINE BLUE	N/est	N/est	N/est	N/est	1.00 mg/M3
N-PROPYL ACETATE	200.00 PPM	N/est	250.00 PPM	250.00 PPM	200.00 PPM
HI FLASH NAPHTHA	25.00 PPM	N/est	N/est	N/est	25.00 PPM
FORMALDEHYDE	0.75 PPM	N/est	N/est	N/est	1.00 PPM

RESPIRATORY PROTECTION - Provide adequate ventilation. If TLV of the product is exceeded, a NIOSH/MSHA jointly approved self-contained breathing apparatus with a full facepiece operated in pressure demand or other positive pressure mode is advised.

VENTILATION - Provide sufficient mechanical and/or local exhaust ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES - Wear resistant gloves such as Buna-N (nitrile rubber).

EYE PROTECTION - Chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE EQUIPMENT - To prevent prolonged skin contact, wear impervious clothing and boots. Maintain an eyewash facility and an emergency shower.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form: LIQUID
 Appearance/Color: BLUE
 Odor: PUNGENT
 Solubility (in water): INSOLUBLE
 pH Value: Not Available
 Boiling Range: 133.0F - 398.0F (56.110C - 203.330C)

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
 MSDS Number: BD-805
 Version Number
 MSDS Date: APR-09-2012
 Page Number: 7 of 10

Vapor Pressure (mmHg): Not Available
 Melting Point: Not Available
 Evaporation Rate: 0.828 times Faster than n-Butyl Acetate
 Vapor Density: Heavier than air
 Partition Coefficient: Not Available
 % Volatile Weight: 65.31%
 % Volatile BY VOLUME 76.33%
 Specific Gravity: 0.98537
 VOC 1.72 VOC/NV LBS
 Molecular Weight: N/A
 Heavy Elements (ppm): 0.

SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable
 Hazardous Polymerization: Hazardous polymerization will not occur

SECTION XI - TOXICOLOGICAL INFORMATION

Route	Species	Exposure and Dose
ISO BUTYL ALCOHOL		
Inhalation	Rat, adult	LC50 8000. PPM
Oral	Rat, adult	LD50 2.5 PPM
ETHYLBENZENE		
Oral	Rat, adult	LD50 3500. PPM
FORMALDEHYDE		
Inhalation	Rat, adult	LC50 250. PPM
Oral	Rat, adult	LD50 800. PPM

THIS PRODUCT CONTAINS ETHYLBENZENE.
 A study conducted by the National Toxicology Program states that lifetime inhalation exposure of rats and mice to high concentrations of ethylbenzene (750 ppm) resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. Incidences of testicular adenoma were increased along with increased incidences of thyroid effects in rats at 750 ppm; pituitary

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
MSDS Number: BD-805
Version Number
MSDS Date: APR-09-2012
Page Number: 8 of 10

effects were observed in female mice at 250 ppm. These effects were not observed in animals exposed to lower concentrations of ethylbenzene (75 ppm). The study does not address the relevance of these results to humans.

Formaldehyde has oral (rat) and dermal (rabbit) LD50 values of 800 mg/kg and 270 mg/kg, respectively. The LC50 following a 4-hour inhalation exposure to rats is 250-478 ppm. Irritation of the nose and throat has been observed in people exposed to formaldehyde vapor levels in excess of 1 ppm. Normal breathing may be seriously impaired at levels above 10 ppm and serious lung damage can occur at levels exceeding 50 ppm. No pulmonary sensitization has been demonstrated in laboratory animal studies. Formaldehyde solutions can cause severe eye and moderate skin irritation. Repeated skin exposure to solutions of 2% or more formaldehyde has caused allergic skin reactions. Formaldehyde was found to be weakly mutagenic in a number of in vitro genotoxicity tests, but inactive in vivo. Formaldehyde did not cause birth defects in rats inhaling concentrations up to 10 ppm. Lifetime inhalation of formaldehyde vapor at concentrations above 5 ppm for 6 hours per day caused nasal tumors in laboratory animals. Epidemiology studies have failed to link cancer in humans with occupational exposure to formaldehyde. Formaldehyde is a chemical known to the State of California to cause cancer.

SECTION XII - ECOLOGICAL INFORMATION

No data available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Empty containers should be washed and discarded.

Empty containers should not be used for other purposes. Disposal should be in accordance with local, state or national legislation.

SECTION XIV - TRANSPORT INFORMATION

UN Number	UN1263
UN Pack Group	II
UN Class	3

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
MSDS Number: BD-805
Version Number
MSDS Date: APR-09-2012
Page Number: 9 of 10

Emergency Storage N/A
MFAG Table Number N/A
Kemmler Code N/A
ICAO/IATA Class N/A
IMDG Class N/A
Shipping Name PAINT, 3, UN1263, II
DOT Hazard Class
Technical Name

SECTION XV - REGULATORY INFORMATION

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
XYLENE	1330-20-7	10.52
ETHYLBENZENE	100-41-4	2.67

ACETONE is not regulated as a VOC under the Clean Air Act.

SECTION XVI - OTHER INFORMATION

NOTICE - Reports have associated repeated and prolonged occupational exposures with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DISCLAIMER:

The information contained herein applies only to the material identified on this MSDS. The data presented in these sheets are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of this product and is accurate to the best of our knowledge at the date of issue of this MSDS. Coating Development Group, Inc. makes no warranty with respect to the accuracy of the information provided by its suppliers and disclaims all

MATERIAL SAFETY DATA SHEET

MSDS Name: BLUE CONV. PRIMER
MSDS Number: BD-805
Version Number
MSDS Date: APR-09-2012
Page Number: 10 of 10

liability of reliance thereon. Coating Development Group, Inc. warrants only that its products conform to their published specifications. We do not guarantee favorable results and we assume no liability in connection with the use of this product. Final determination of the use of this product is the sole responsibility of the user. Although certain hazards are described herein, it cannot be guaranteed that these are the only hazards that exist. All chemicals may present unknown health hazards and should be used with caution. Read all labels.